


AXIS R7



TECHNICAL DATA

Application	Inground Uplight
Location	Outdoor
Light Source	LED
Optics	15°, 24°, 36°
LED No.	1
LED Life time (L80B10)	50000 hours
Input Voltage / Current	24V DC
Connection details	Parallel Connection
Installation	Recessed (Ceiling, Wall, Floor) Brick work installation with housing box (not included) Panel installation with torsion spring (not included)
Installation hole	Ø111mm(with springs) - Ø111mm(with housing box)
Supply	24Vdc
Wiring	Provided with 150cm neoprene cable
Working Temperature	-20°C - +50°C



FINISHING

Materials	Anodized aluminium body, anodized aluminum or AISI 316L Stainless steel trim, tempered glass diffuser
Finishing	Anodized Aluminum (A), Worked Steel (I), Satinized Steel(S), Anodized Black (J)
Color	Matte Steel
Diffuser	Tempered Glass

Family	Type	LED NO	WATT/LED	CCT	Optics	Finish	Power	Dimming	Options
AX- Axis	R7 - Round	1	11	27-2700K 30-3000K 40-4000K 50-5000K XX- Custom	15 - 15° 24 - 24° 36 - 36°	I - Worked Steel	CV	N - None	XXX

Sample: AX - R7 - 1 - 11 - 27 - 15 - I - CV - N - XX

ACCESSORIES

Cainster - Casing Polypropylene Adjustable Optional

XXX

