


Aries

TECHNICAL DATA

| | |
|-------------------------|------------------------------------|
| Application | Floor Mounted Bollard |
| Location | Outdoor |
| Light Source | LED |
| Optics | 120° |
| Lumen | 30lm/W |
| LED Life time (L80B10) | 50000 hours |
| Input Voltage / Current | 220-230V AC 50-60Hz |
| Connection details | Parallel Connection |
| Installation | Floor mounted |
| Weight | 3.8kg |
| Supply | 220-230V AC |
| Wiring | Provided with 150cm neoprene cable |
| Working Temperature | -20°C - +50°C |



FINISHING

| | |
|-----------|---|
| Materials | Heavy duty die cast aluminium |
| Finishing | Die cast aluminium with tempered glass diffuser |
| Color | Teak wood ,Grey Finish |
| Diffuser | Tempered Glass |

| Family | Type | WATT/LED | CCT | Optics | Finish | Power | Dimming | Options |
|----------|----------------|----------|--|------------|------------------------|-------------|----------|---------|
| AR-Aries | RE - Rectangle | 13 - 13W | 27-2700K 30-3000K 40-4000K 50-5000K | 120 - 120° | WD - Wood GR - Grey | AC - 230VAC | N - None | |

Sample: AR - RE - 13 - 27 - 120 - WD - AC - N

ACCESSORIES