



Arena L



TECHNICAL DATA

Application	Surface mounted (Wall, Floor)
Location	Outdoor/ Indoor
Light Source	LED
Optics	5°, 10°, 15°, 24°, 36°, 60°, 90°, 10° x 40°, 10° x 90°
LED Life time (L80B10)	50000 hours
Input Voltage / Current	100-240V AC(43-60Hz)
Control Gear	In-built
Connection details	Parallel Connection
Installation	Surface mounted (Wall, Floor)
Weight	4,0Kg
Dimension	L1000 x W 60 x H 79mm
Supply	95-265V AC, 24/48V DC
LED Module	High-power LEDs on metal-core PCB. Collimating lens made of optical polymer/pmma
Anti-Glare	Option
Electric Protection	EMC, inrush current
Electrical Class	3
Working Temperature	-20°C - +50°C



FINISHING

Materials	Die-cast aluminium,
Finishing	Grey, White, Black
Diffuser	Tempered Glass

Family	Type	WATT/Mtr	CCT	Optics	Finish	Power	Dimming	Options
AR-Arena	L - Linear	48 - 48	22 - 2200K	5 - 5°	GR - Anodised Grey	AC - 240V AC	DX - DMX512	
		60 - 60	27 - 2700K	10 - 10°	WH - White	24 - 24V	DA - Dali	
		100 - 100	30 - 3000K	15 - 15°	BK - Black	48 - 48V	AN - 1-10V	
			40 - 4000K	24 - 24°	XX - Custom		ND - Non-Dim	
		50 - 5000K	36 - 36°					
		60 - 6000K	60 - 60°					
		RGB - RGB	90 - 90°					
		RGBW - RGBW	10x40 - 10°x40°					
		XX - Custom	10x90 - 10°x90°					

Sample: AR - L - 48 - 22 - 5 - GR - AC - DX

**Dali/AN/ND- only for Mono Color
RGB/RGBW-available only in DMX

**Standard 1000mm Fixture
Custom length are available