




# DOVER R



## TECHNICAL DATA

Application	Inground uplight
Location	Indoor / Outdoor
Light Source	LED
Optics	Narrow, Medium, Wide
LED No.	1
LED Life time	50000 hours
Connection details	Parallel Connection
Installation	Inground, with housing box (not included)
Supply	100-277V
Wiring	Provided with 150cm neoprene cable
Working Temperature	-30°C - +50°C



## FINISHING

Materials	Anodized aluminium body, anodized aluminum or AISI 316L Stainless steel trim, tempered glass diffuser
Finishing	Anodized Aluminum (A), Worked Steel (I), Satinized Steel(S), Anodized Black (J)
Color	Matte Steel
Diffuser	Tempered Glass


Family	Type	LED NO	WATT	CCT	Optics	Finish	Power	Dimming	Options
DO - Dover	R - Round	1	8	27-2700K	N - Narrow	A - Anodized Aluminum	AC- 100-277V	D - Dimmable	XXX
			12	30-3000K	M - Medium	I - Worked Steel			
			26	40-4000K	W - Wide	S - Satinized Steel			
				50-5000K					

Sample: DO - R - 1 - 8 - 27 - N - A - AC - D - XX

## ACCESSORIES




Recessed Box



Honeycomb



IP68 Connector



Square Cover