

Lutron SP

CE IP68





Kg 0,200



TECHNICAL DATA

| | |
|-------------------------|---|
| Application | Surface mounted (Ceiling, Wall, Floor, Ground) |
| Location | Outdoor |
| Light Source | LED |
| Optics | Very Narrow, Narrow, Medium, Wide |
| LED No. | 1 |
| LED Life time (L80B10) | 50000 hours |
| Input Voltage / Current | 100-277V / 24V DC |
| Installation | Surface mounted (Ceiling, Wall, Floor, Ground) |
| Supply | 100-277V / DC24V |
| Wiring | Provided with 50cm neoprene cable |
| Working Temperature | -30°C - +50°C |




FINISHING

| | |
|-----------|--|
| Materials | Anodized aluminium,AISI316Lstainless steel bracket, tempered glass diffuser |
| Finishing | Black (B), Grey (G), Custom |
| Diffuser | Tempered Glass |


| Family | Type | LED NO | WATT | CCT | Optics | Finish | Power | Dimming | Options |
|-------------|------------|--------|------|----------|------------------|------------|---------------|-------------|------------------|
| LU - Lutron | SP - Spike | 1 | 4.5 | 27-2700K | VN - Very Narrow | B - Black | AC - 100-277V | D - Dimming | HCL - HoneyComb |
| | | | 7 | 30-3000K | N - Narrow | G - Grey | DC - DC24V | | SP - Spike |
| | | | 12 | 40-4000K | M - Medium | X - Custom | | | AB - Anchor Belt |
| | | | | 50-5000K | W - Wide | | | | |

Sample: LU - SP - 1 - 4.5 - 27 - VN - B - AC - D - HCL

ACCESSORIES



Spike



HoneyComb



Anchor Belt